Regulated DC-DC Converter — 150 × 110 × 49 mm Case, 9–40 V to 24 V

Regulated (stabilised) converter for 9–40 V DC systems, supplying 24 V at 25 A in one sealed aluminium case.

KEY FEATURES

- Input versions — **24 V (9–40 V)**
- Outputs at **24 V**, held to ± 0.25 V
- **25 A** in this case — 600 W
- **150 × 110 × 49 mm** finned heat-sink case; housing machined to order
- **93 % transfer efficiency** at rated load
- **IP67** — dust-tight, immersion to 1 m for 30 min
- Short-circuit, over-current, over-voltage and over-temperature protection
- Certified to **CE, FCC and RoHS**

MODELS BUILT IN THIS CASE

Model	Input version	Output current	Output power
9V/40V-24V	24 V (9–40 V)	25 A	600 W

Ordering model = model prefix + current rating, i.e. **9V/40V-24V 25A**. Output power is the rated output voltage multiplied by the output current. All models use the same 150 × 110 × 49 mm case.

ELECTRICAL SPECIFICATION

Input voltage	DC 24 V (9–40 V)
Output voltage	24 V, held to ± 0.25 V
Output current	25 A in this case
Output power	600 W in this case
Transfer efficiency	93 % typical at rated load
Protection	Short-circuit, over-current, over-voltage, over-temperature

Ripple and noise, no-load input current and MTBF are not published for this case size — available on request.

MECHANICAL AND COMPLIANCE

Case size (mm)	150 × 110 × 49
Ingress protection	IP67 — sealed housing, no vents or fan intake
Working temperature	-40 °C to +80 °C
Storage temperature	-40 °C to +100 °C
Working humidity	10 % to 90 % RH
Certification	CE, FCC, RoHS
Warranty	2 years standard, extendable by agreement

Custom housing — outline issued after order review.

Custom requirements. If the model you need is not listed, send input range, output voltage, output current, case or terminal preference and quantity — we will quote a customized build.

© 2026 Guangzhou VOITA Electronic Technology Co., Ltd. · www.voitatech.com

inquiry@voitatech.com · +86 191 5742 1386