Step-up DC-DC Converter — 150 × 127 × 63 mm Case, 24 V / 48 V Output

Step-up converter for 12 V and 24 V DC systems: 9–16 V or 18–45 V DC input, 24 V or 48 V DC output at 15 A to 30 A (720 W to 1440 W), in one sealed IP67 case with INPUT / GND / OUTPUT studs.

KEY FEATURES

- Input **DC 12 V (9–16 V)** or **DC 24 V (18–45 V)**
- Output **24 V or 48 V**, held to ± 0.25 V
- **15 A to 30 A** in this case — 720 W to 1440 W
- **150 × 127 × 63 mm** finned heat-sink case, **1.5–1.6 kg**
- **90 % transfer efficiency** at rated load
- **IP67** — dust-tight, immersion to 1 m for 30 min
- Over-current and over-heating protection, cut-off at 150 °C
- Working temperature **−20 °C to 85 °C**; certified to **CE, FCC and RoHS**

MODELS BUILT IN THIS CASE

Model	Input version	Output current	Output power
12V-24V	12 V (9–16 V)	30 A	720 W
12V-48V	12 V (9–16 V)	15 A	720 W
24V-48V	24 V (18–45 V)	30 A	1440 W

Ordering model = voltage pair + current rating, e.g. **24V-48V 30A**. Output power is the rated output voltage multiplied by the output current. Other voltage pairs of the same series are built in the 66 × 58 × 23 mm, 74 × 74 × 32 mm, 100 × 80 × 38 mm and 220 × 127 × 63 mm cases.

ELECTRICAL SPECIFICATION

Input voltage	DC 12 V (9–16 V) or DC 24 V (18–45 V)
Output voltage	24 V or 48 V, held to ± 0.25 V
Output current	15 A to 30 A in this case
Output power	720 W to 1440 W in this case
Transfer efficiency	90 % typical at rated load
Protection	Over-current, over-heating; cut-off at 150 °C
Working temperature	−20 °C to 85 °C

Ripple and noise, no-load input current and MTBF are not published for this case size — available on request.

MECHANICAL AND COMPLIANCE

Case size (mm)	150 × 127 × 63
Net weight	1.5–1.6 kg
Housing	Finned aluminium extrusion, sealed
Terminals	Three threaded studs, marked INPUT / GND / OUTPUT
Mounting slots	5 mm wide, Ø 5 mm holes, 75 mm from the edge
Ingress protection	IP67 — sealed housing, no vents or fan intake
Certification	CE, FCC, RoHS
Warranty	2 years standard, extendable by agreement



Plan view, dimensions in mm — 150 × 127 × 63, 5 mm slots with Ø 5 mm holes.

Custom requirements. If the model you need is not listed, send input range, output voltage, output current, case or connector preference and quantity — we will quote a customized build.

© 2026 Guangzhou VOITA Electronic Technology Co., Ltd. · www.voitatech.com
inquiry@voitatech.com · +86 191 5742 1386